

Machines for MMA welding

MMA

Inverter devices of the *inverter* STICK series



inverter **STICK 200 powerSinus** 1 x 230V 200A/25%ED

inverter **STICK 250 H-2** 3 x 400V 250A/60%ED

inverter **STICK 300 CEL, PWS** 3 x 400V 300A/40%ED

inverter **STICK 350 ,PWS** 3 x 400V 350A/60%ED

inverter **STICK 450** 3 x 400V 450A/60%ED

Machines for MMA welding

Inverter devices of the *inverter* STICK series

Features	Advantages for the user/client
lightweight	easy handling and transportation
generator-suitable	mains-independent
Hotstart	ignition and re-ignition without problems
flexible	adjustable Arcforcing for excellent welding characteristics for all electrode types
Antistick	current lowering after "freezing" of the electrode
dropped seam-proof	easy vertical-down welding even with cellulose electrodes (300CEL, 350).
remote-control socket	flexible for specialized applications
units with STICK/TIG	wide variety of possible applications
STICK 200 powerSinus	200A from normal 230V socket, cos phi 1, mains voltage tolerance -40%/+15% (138V-264V).
S-sign	application possible at increased electrical risk



Machines for MMA welding


inverter STICK 300 CEL PWS Remote Controls




- **Excellent welding characteristics**
 - High electrode recovery
 - No welding breaks
 - 100% dropped seam-proof, even with difficult cellulose- electrodes
- **All-purpose devices with adjustable arcforcing for outstanding welding characteristics with the different electrode types (rutile, basic, cellulose).**
- **Easy working by polarity-switching at the device or with remote control.**
 - Remote controls optimally adjusted to the application
 - FR30 F(PWS): setting ranges coarse/fine, polarity switch; important in tube and pipeline construction
 - FR30KL: cordless remote control, no cable mess; application e.g. in shipbuilding, Off-Shore and others
 - FR 35: Individual setting of Hotstart current and time

Machines for MMA welding


MMA Characteristic



Hotstart



Arcforcing



Antistick

